

RETREAD SPECIFICATIONS

The specs listed below are a recommendation only. Buffing equipment can vary and, as such, the specs below should be verified for each different style of buffer. Buff profile should be verified using pilot skives of 3/32" across buffed tread surface.

Size	Pattern	Buffed Crown Radius		Buffed Crown Width		Rim Width
		mm	in	mm	in	in
11R22.5	RSL1	660.0	26.0	220.0	8.66	8.25
11R24.5		660.0	26.0	220.0	8.66	8.25
295/75R22.5		711.0	28.0	220.0	8.66	9.00
285/75R24.5		711.0	28.0	220.0	8.66	8.25
12R22.5	RSR6	610.0	24.0	230.0	9.06	8.25
315/80R22.5		762.0	30.0	240.0	9.45	9.00
11R22.5	RTL1	660.0	26.0	210.0	8.27	8.25
11R24.5		660.0	26.0	210.0	8.27	8.25
295/75R22.5		711.0	28.0	220.0	8.66	9.00
285/75R24.5		711.0	28.0	210.0	8.27	8.25
11R22.5	RTL2	1321.0	52.0	225.0	8.86	8.25
11R24.5		1321.0	52.0	225.0	8.86	8.25
295/75R22.5		813.0	32.0	225.0	8.86	9.00
285/75R24.5		813.0	32.0	225.0	8.86	8.25
215/75R17.5	RSR4	559.0	22.0	160.0	6.30	6.00
235/75R17.5		660.0	26.0	180.0	7.09	6.75
225/70R19.5		711.0	28.0	180.0	7.09	6.75
245/70R19.5		711.0	28.0	200.0	7.87	7.50
255/70R22.5		711.0	28.0	200.0	7.87	7.50
275/70R22.5		762.0	30.0	230.0	9.06	8.25
245/70R17.5		711.0	28.0	200.0	7.87	6.75
255/70R22.5	711.0	28.0	200.0	7.87	7.50	
275/70R22.5	762.0	30.0	230.0	9.06	8.25	
11R22.5	RSR7	660.0	26.0	220.0	8.66	8.25
11R24.5		610.0	24.0	220.0	8.66	8.25
295/75R22.5		711.0	28.0	220.0	8.66	9.00
285/75R24.5		711.0	28.0	220.0	8.66	8.25
215/75R17.5	RSR4SP	559.0	22.0	175.0	6.89	6.00
225/70R19.5		711.0	28.0	185.0	7.28	6.75
245/70R19.5		711.0	28.0	225.0	8.86	7.50
225/70R19.5	RDR3	813.0	32.0	180.0	7.09	6.75
245/70R19.5		711.0	28.0	200.0	7.87	7.50
11R22.5	RDR4	660.0	26.0	220.0	8.66	8.25
11R24.5		610.0	24.0	220.0	8.66	8.25
255/70R22.5		711.0	28.0	200.0	7.87	7.50
11R22.5	RDR6	660.0	26.0	220.0	8.66	8.25
11R24.5		610.0	24.0	220.0	8.66	8.25
11R22.5	RDM2	660.0	26.0	220.0	8.66	8.25
11R24.5		610.0	24.0	220.0	8.66	8.25

Size	Pattern	Buffed Crown Radius		Buffed Crown Width		Rim Width
		mm	in	mm	in	in
11R22.5	RDL1	660.0	26.0	220.0	8.66	8.25
11R24.5		660.0	26.0	220.0	8.66	8.25
295/75R22.5		711.0	28.0	220.0	8.66	9.00
285/75R24.5		711.0	28.0	220.0	8.66	8.25
11R22.5	RDL2	711.0	28.0	240.0	9.45	8.25
11R24.5		711.0	28.0	240.0	9.45	8.25
295/75R22.5		762.0	30.0	240.0	9.45	9.00
285/75R24.5	762.0	30.0	240.0	9.45	8.25	
11R22.5	RDL3	1016.0	40.0	225.0	8.86	8.25
11R24.5		1016.0	40.0	225.0	8.86	8.25
295/75R22.5		660.0	26.0	225.0	8.86	9.00
285/75R24.5		813.0	32.0	225.0	8.86	8.25
255/70R22.5	RAM2	711.0	28.0	200.0	7.87	7.50
275/70R22.5		762.0	30.0	230.0	9.06	8.25
315/80R22.5		762.0	30.0	230.0	9.06	9.00
11R22.5	RAM3	660.0	26.0	225.0	8.86	8.25
11R24.5		610.0	24.0	225.0	8.86	8.25
11R22.5	RDW1	711.0	28.0	235.0	9.25	8.25
11R24.5		711.0	28.0	235.0	9.25	8.25
11R22.5	RDM1	660.0	26.0	220.0	8.66	8.25
11R24.5		660.0	26.0	220.0	8.66	8.25
11R22.5	RDM3	660.0	26.0	220.0	8.66	8.25
11R24.5		660.0	26.0	220.0	8.66	8.25
315/80R22.5		838.0	33.0	265.0	10.43	9.00
385/65R22.5	RAR8-WB	1067.0	42.0	310.0	12.20	11.75
425/65R22.5		1067.0	42.0	330.0	12.99	12.25
385/65R22.5	RAR7-WB	1067.0	42.0	315.0	12.40	11.75
385/55R22.5		991.0	39.0	335.0	13.19	12.25
225/70R19.5	RDR5SP	813.0	32.0	190.0	7.48	6.75
245/70R19.5		711.0	28.0	200.0	7.87	7.50
11R22.5	RAM1	660.0	26.0	220.0	8.66	8.25
11R24.5		610.0	24.0	220.0	8.66	8.25
11R22.5	RTR2	660.0	26.0	220.0	8.66	8.25
11R24.5		660.0	26.0	220.0	8.66	8.25
255/70R22.5		711.0	28.0	210.0	8.27	7.50
295/75R22.5		711.0	28.0	220.0	8.66	9.00
445/50R22.5	RTL52	1245.0	49.0	400.0	15.75	14.00
445/50R22.5	RDL51	1245.0	49.0	400.0	15.75	14.00